

Waveguide to Coax Adapters

Type N Standard Adapters

VSWR is 1.25 maximum.

FREQ. RANGE GC/SEC.	MDL MODEL NUMBER	FIG.	DIMENSIONS		
			"A" MAX.	"B" MAX.	"C" +.020
10.00-15.00	75AC46*	1	1.20	1.00	0.87
	75AC56*	2	1.20	1.09	0.87
8.20-12.40	90AC46*	1	1.15	1.02	0.88
	90AC56*	2	1.15	1.11	0.88
7.00-11.00	102AC46*	1	1.40	1.08	1.06
	102AC56*	2	1.40	1.17	1.06
7.05-10.00	112AC46*	1	1.40	1.07	1.06
	112AC56*	2	1.40	1.16	1.06
5.85-8.20	137AC46* ⁺	1	1.72	1.40	1.31
	137AC56* ⁺	2	1.72	1.49	1.31
4.90-7.05	159AC46*	1	1.90	1.92	1.40
	159AC56*	2	1.90	2.01	1.40
3.95-5.85	187AC46* ⁺	1	1.97	1.96	1.45
	187AC56* ⁺	2	1.97	2.05	1.45
3.30-4.90	229AC46*	1	2.70	2.08	1.97
	229AC56*	2	2.70	2.17	1.97
2.60-3.95	284AC46* ⁺	1	2.72	2.19	1.87
	284AC56* ⁺	2	2.72	2.28	1.87
1.70-2.30	430AC46*	1	4.00	2.59	3.08
	430AC56*	2	4.00	2.65	3.08
1.12-1.70	650AC46*	1	5.30	5.60	2.68

Notes: ⁺ Flanges are round, not square as shown.

* See ordering information page 61

TYPE N STANDARD ADAPTERS

