


"I" Style Rotary Joints

"I" (inline) Style, two opposite arms vscentric with the axis of rotation-one fixed to the housing-one free to rotate.

BAND	FREQ. RANGE GHz	MDL MODEL	VSWR MAX	WOW MAX	INSERTION LOSS MAX	PEAK POWER AT				CW	HOUSING DIA.	HGT
						0	15	30	45			
						PRESSURE (PSIG)						
WR22	43.50 - 45.50	22RJ16	1.50	1.05	1.00	20	50	80	-		1.99	3.23
WR42	20.20 - 21.20	42RJ16	1.50	1.05	1.00	30	65	120	-		1.25	3.00
WR62	13.50 - 14.05	62RJ126	1.15	1.02	0.10	30	60	120	-		1.81	3.00
	13.50 - 14.50	62RJ136	1.15	1.02	0.10	75	165	300	-		1.81	3.00
	14.00 - 15.00	62RJ146	1.10	1.02	0.10	30	60	120	-		1.81	3.00
	14.00 - 15.00	62RJ156	1.15	1.02	0.10	75	165	300	-		1.81	3.00
	14.50 - 15.50	62RJ166	1.10	1.02	0.10	30	60	120	-		1.81	3.00
	14.50 - 15.50	62RJ176	1.15	1.02	0.10	75	165	300	-		1.81	3.00
	15.00 - 16.00	62RJ186	1.10	1.02	0.10	30	60	120	-		1.81	3.00
	15.00 - 16.00	62RJ196	1.15	1.02	0.10	75	165	300	-		1.81	3.00
	15.50 - 16.50	62RJ206	1.10	1.02	0.10	30	60	120	-		1.81	3.00
	15.50 - 16.50	62RJ216	1.15	1.02	0.10	75	165	300	-		1.81	3.00
	16.00 - 17.00	62RJ226	1.10	1.02	0.10	30	60	120	-		1.81	3.00
	16.00 - 17.00	62RJ236	1.15	1.02	0.10	75	165	300	-		1.81	3.00
	13.50 - 17.50	62RJ246	1.35	1.03	0.15	30	60	120	-		1.81	3.00
	13.50 - 15.50	62LM16	1.15	1.02	0.10	150	330	600	-		1.62	1.10
WR75	14.00 - 14.50	75RJ16	1.10	1.02	0.10	75	165	300	-		1.50	3.50
	13.75 - 14.50	75RJ26	1.10	1.02	0.10	30			600 W		1.27	3.50
WR90	8.20 - 9.00	90RJ246	1.10	1.02	0.10	175	350	675	-		1.81	3.29
	8.20 - 9.00	90RJ256	1.10	1.02	0.10	250	500	950	-		1.81	3.29
	8.50 - 9.60	90RJ266	1.10	1.02	0.10	175	350	675	-		1.81	3.29
	8.50 - 9.60	90RJ276	1.10	1.02	0.10	250	500	950	-		1.81	3.29
	9.00 - 10.00	90RJ286	1.10	1.02	0.10	175	350	675	-		1.81	3.29
	9.00 - 10.00	90RJ296	1.10	1.02	0.10	250	500	950	-		1.81	3.29
	9.50 - 10.50	90RJ306	1.15	1.02	0.10	175	350	675	-		1.81	3.29
	10.00 - 11.00	90RJ316	1.15	1.02	0.15	175	350	675	-		1.81	3.29
	8.20 - 10.00	90RJ326	1.25	1.04	0.15	175	350	675	-		1.81	3.29
	8.20 - 11.00	90RJ336	1.35	1.05	0.15	150	300	575	-		1.81	3.29
WR112	7.20 - 8.20	112RJ146	1.10	1.02	0.10	200	400	775	-		2.25	4.00
	7.50 - 8.50	112RJ156	1.10	1.02	0.10	200	400	775	-		2.25	4.00
	7.50 - 8.50	112RJ166	1.15	1.02	0.10	275	550	1050	-		2.25	4.00
	8.00 - 9.00	112RJ176	1.10	1.02	0.10	200	400	775	-		2.25	4.00
	8.00 - 9.00	112RJ186	1.15	1.02	0.10	275	550	1050	-		2.25	4.00
	8.50 - 9.60	112RJ196	1.10	1.02	0.10	200	400	775	-		2.25	4.00
	8.50 - 9.60	112RJ206	1.15	1.02	0.10	275	550	1050	-		2.25	4.00
	9.00 - 10.00	112RJ216	1.10	1.02	0.10	200	400	775	-		2.25	4.00
	8.00 - 10.00	112RJ226	1.20	1.03	0.10	200	400	775	-		2.25	4.00
WR137	5.80 - 6.80	137RJ26	1.10	1.02	0.10	350	700	1350	1925		2.62	4.98
	6.50 - 7.50	137RJ36	1.15	1.02	0.10	350	700	1350	1925		2.62	4.98
	5.80 - 7.80	137RJ46	1.30	1.03	0.15	350	700	1350	1925		2.62	4.98
	5.80 - 8.40	137RJ56	1.20	1.05	0.20					1.6 KW	2.76	4.98
	5.85 - 6.425	137RJ66	1.20	1.05	0.20					6 KW	2.76	4.98
WR159	5.80 - 6.40	159RJ26	1.15	1.02	0.10	400	800	1525	2200		3.00	5.65



"I" Style Rotary Joints

BAND	FREQ. RANGE GHz	MDL MODEL	VSWR MAX	WOW MAX	INSERTION LOSS MAX	PEAK POWER AT PRESSURE (PSIG)				CW	HOUSING DIA.	HGT
						0	15	30	45			
WR187	5.4 - 5.9	187RJ66	1.10	1.02	0.10	450	900	1725	2500		3.00	6.66
	5.25 - 6.0	187RJ86	1.20	1.03	0.10	450	900	1725	2500		3.00	6.66
	4.8 - 5.2	187RJ96	1.15	1.02	0.10	450					3.00	6.66
WR229	3.6 - 4.3	229RJ26	1.15	1.02	0.10	550	1100	2100	3025		3.44	7.49
WR284	2.7 - 3.2	284RJ26	1.15	1.02	0.10	700	1400	2650	3850		4.63	9.89
	2.7 - 3.2	284RJ36	1.15	1.02	0.10	700	1400	2650	3850		4.63	9.26
	2.7 - 3.2	284RJ46	1.15	1.02	0.10	700	1400	2650	3850		4.63	10.51
	2.7 - 3.2	284RJ56	1.15	1.02	0.10	700	1400	2650	3850		4.63	9.89
	3.0 - 3.5	284RJ106	1.25	1.02	0.10			1300		4.5 KW	4.63	9.37

